



Feature

- Attractive outlook
- 1/3" SONY CCD
- Water Resistance : IP66
- Built-in bracket, 3-Axis direction bracket
- Others function : AWB, WDR, OSD
- Low Illumination, 600TV Lines

Specifications

Model	LE-KT40S	LE-KT90S
Pixels	PAL:795 (H)x 596(V) NTSC :811 (H)x508 (V)	
Image Sensor	1/3"SONY CCD	
Horizontal Resolution	600TV Lines	
Usable Illumination	0 Lux/F2.0 (LED ON)	
S/N Ratio	>48dB (AGC OFF)	
White Balance	Auto	
Len	4-9mm Manual Zoom lens	8-20mm Manual Zoom lens
Synchronization System	Internal	
Video Output	Composite Signal (1.0Vp-p 75 Ω BNC)	
IR Power On	CDS Auto Control	
IR LED	φ 5 X 42 PCS	φ 5 X 72 PCS
IR series Distance	40M	60M
IR Status	Under 10 Lux By CDS	
Power supply	DC12V 500mA	DC12V 700mA
Operation Temperature	-10℃ ~ +50℃ RH95% Max	
Dimension	228(W) x97(H) x 82(D)mm	259(W) x120(H) x 103(D)mm
Net Weight	1200g	1400g

Specifications and dimensions subject to change without notice.

Lifecom Technologies (HK) Co., Ltd.

Tel. : 3589 6755 Fax: 3427 3318 E-mail: info@lifecomhk.com Web-Site: www.lifecomhk.com