

LE-R899/LE-R8916 (H.264, 9 / 16CH DVR)



Digital Security System

PERFORMANCE & RELIABILITY

H.264



Feature :

- 9/16 CH H.264 DVR with sixfold operation-record, live, playback, backup, control & time display
- H.264 Baseline profile video compression / decompression with configurable quality
- Bi-directional audio capabilities
- Ethernet X 1 for remote access, including web access, e-mail alarm notification, FTP video / audio file storage and software upgrade
- USB 2.0 for video / audio backup to versatile USB2.0 Storage devices
- Dust filter for harsh environments
- Multi-lingual support for setup and display
- Supports mouse and remote control
- Open system architecture for ease of access via network, RS-485
- Support mobile phone, WAP protocol





LE-R899/LE-R8916 (H.264, 9 / 16CH DVR)



FUNCTIONAL SPECIFICATIONS

Description		Specification	
		LE-R899	LE-R8916
Video	Video Input	9 Channels Independent Input with 1.0Vp-p, 75 Ω BNC	16Channels Independent Input with 1.0Vp-p, 75 Ω BNC
	Video Output	2ch PAL/NTSC Output with 1.0Vp-p, 75 Ω BNC, Composite Video Signal 1ch VGA Display Output	
Audio	Audio Input/Output	2ch Input and 2ch output	
Digital Processing and Storing	Compression	H.264	
	Audio	ADPCM	
	Storage	Over 250G bytes, SATA HDDs x 4	
Record	Recording Time	around 20days with 500GB HD @25fps for continuous recording mode	
	Recording Mode	Continuous, motion detection, sensor activated, time schedule	
Resolution	Display	NTSC: 720X480, PAL:720X576	
	Recording	NTSC: 60/720x480, 120/720x240, 240/360x240 PAL: 50/720x576, 100/720x288, 200/360x288	
Sensors, Alarm	Output	9 input, 4 Output	16 input, 4 Output
Frame rate	Recording (FPS)	200 fps	
Network	Network interface	RJ-45	
PTZ	Pan/Tilt/Zoom	RS-232 / RS-485	
Archiving	Back-up	2 USB 2.0 ports for USB 2.0 disk drives, DVD+RW, DVD+R, DVD-R, Card readers, HDD, etc. Internal DVD models: DVD+RW, DVD+R, DVD-R	
F/W upgrade	Network / USB2.0	Firmware Upgrade via USB, network	
Other	Power	AC 220V ($\pm 20\%$) 、 50Hz ($\pm 2\%$)	
	Working Temperature	0~+45 $^{\circ}$ C	

The above specification can be changed without previous notice for improvement of product.

Lifecom Technologies (HK) Co., Ltd.

Tel. : 3589 6755 Fax: 3427 3318 E-mail: info@lifecomhk.com Web-Site: www.lifecomhk.com